



OPTIDRIVE™ CP²

AC Variable Speed Drive

Powerful Performance Advanced motor control



0.75kW–250kW / 1HP–350HP
200–600V Single & 3 Phase Input

Powerful Performance

World leading control for the latest generation of permanent magnet and standard induction motors

Manufacturing Conveyer Systems Processing Plants Chemical
Pumping Plastics Rubber Machine Tools Elevators Cranes



World Leading Motor Control

The Optidrive P2 offers the perfect combination of high performance together with ease of use to allow even the most demanding applications to be tackled easily.

Designed for fast installation and commissioning, Optidrive P2 provides the most cost effective solution for industry.

All Optidrive P2 units provide 150% overload for 60 seconds as standard, ensuring each drive is suitable for Heavy Duty applications, whilst the IP55 enclosed versions ensure the drive is tough enough to survive in industrial environments.

Extensive I/O and communications interface capabilities ensure the drive can be integrated quickly and efficiently into a wide variety of control systems with the minimum commissioning time, ensuring rapid start up. Invertek's simple parameter structure, and carefully selected factory parameter settings ensure that commissioning time is kept to a minimum.



Compliant with international standards.
Manufactured in the UK.

150% overload for
60 seconds



IP20

Up to 250kW



IP55

Up to 160kW



IP66

Up to 30kW

Advanced Motor Control

Optidrive P2 has been uniquely developed to allow a wide range of different motor types to be used, with only parameter changes being required. This technology allows the same drive to be used in a wide range of applications, allowing OEMs and end user alike to take advantage of the energy saving provided by using the latest motor technologies.

AC Induction Motors

The majority of AC motors in use today around the world are standard induction motors. These motors are relatively low cost, readily available and provide good performance with long service life. With the ever increasing focus on energy efficiency, motor manufacturers have refined and improved their designs in recent years.

Optidrive P2 has been developed to provide optimum control and maximum efficiency when operating with older motors designs, or newer high efficiency designs.

Operation can be in simple V/F control mode or in High Performance Third Generation Vector Mode, which provides up to 200% torque from zero speed without requiring an encoder.

Permanent Magnet AC Motors

Permanent magnet AC motors provide improved efficiency compared to standard induction motors. Using permanent magnets in the motor construction eliminates the need for any magnetising current, reducing electrical losses. PM motors have been used for many years in high performance applications, however this has always required the use of a feedback device, such as a resolver or encoder. Optidrive P2 has been designed to operate with AC PM motors without requiring any feedback device, allowing them to be used for their energy efficiency benefits without incurring extra cost and complexity in applications which do not require position feedback.

Brushless DC Motors

BLDC motors are similar to AC PM motors, however the design requires a slightly different control method to optimise the performance. Optidrive P2 has the flexibility to control this type of motor, requiring only simple parameter changes. This provides much greater flexibility for OEMs, allowing Optidrive P2 to be used in a variety of applications, with various motor types.

Synchronous Reluctance Motors

Synchronous Reluctance Motors (SynRM), not to be confused with Switched Reluctance Motors, share a similar stator construction to standard induction motors, however the rotor is substantially different, in order to improve the overall efficiency of the motor. SynRM motors are ideally suited to variable torque applications.


Optidrive P2 can control synchronous reluctance motors, allowing the energy saving benefits to be realised.

At a Glance...

High performance, excellent usability and flexible to meet the needs of your application

Keyhole
Mounts for fast
installation

Integrated
Keypad &
Display



IP55 / NEMA 12

Integrated
EMC Filter



Pluggable Control
Terminals



High Quality
Long-life Fans

Integrated Cable
Management



Integral
Brake
Transistor



Safe Torque Off (provided as standard)	With	Without
<p>Optidrive P2 features a safe torque off function to allow simple integration into machine critical safety circuits.</p> <ul style="list-style-type: none"> Simple machine design reduces component costs, saves panel space and minimises installation time Faster shut down and reset procedures reduce system maintenance time Better safety standard compared to mechanical solution Better motor connection. Single cable with no interruption. 	<p>The diagram shows a "Supply" line connected to an "Emergency stop" button, a "Safety Relay", and the "Machine Safety Circuit" of the Optidrive P2. The Optidrive P2 is connected to a motor. The "Input Contactor NOT required" label indicates that the Optidrive P2 handles the power switching.</p>	<p>The diagram shows a "Supply" line connected to an "Emergency stop" button, a "Safety Relay", and a "Variable Speed Drive". The "Variable Speed Drive" is connected to a motor. This configuration requires an external input contactor.</p>

Applications

High performance, accurate motor control for even the most demanding of applications



Mining & Quarrying

- Feed conveyers
- Crushers
- Cranes

Metals & Processing

- Grinding
- Cutting
- Polishing
- Drilling
- Rolling

Rubber & Plastics

- Extruders
- Moulding
- Mixers
- Winding

Food & Beverage

- Conveyers
- Pumps
- Mixers
- Palletisers

Powerful, versatile and
easy to use



Cranes

Requirements:

- High starting torque
- Smooth motor operation throughout starting and stopping phases
- Motor holding brake control
- Avoidance of load droop and sag
- Regeneration and braking capability during load lowering

Optidrive P2 provides:

- Dedicated Hoist Mode Operation with motor holding brake control algorithm
- Up to 200% torque from zero speed in vector operation without encoder feedback
- Multiple Preset Speed or variable speed operation
- Built in dynamic braking transistor, requires only an external resistor



Compressors

Requirements:

- Precise regulation of speed to ensure a consistent end product
- High starting torque demand in many applications
- Maximum efficiency under all conditions
- Safe operation to prevent accidents and injuries

Optidrive P2 Provides:

- PM Motor control mode to allows open loop operation with Permanent Magnet motors for maximum efficiency
- Maximum starting torque with standard AC motors
- Better than 0.5% speed holding accuracy in Open Loop Vector Operation
- Dedicated Safe Torque Off input complies with EN62061 SIL Level 2 for safe operation



Winding

Requirements:

- Precise control of motor torque over a broad speed range
- Accurate control of material tension under all conditions
- Open or closed loop control capability, based on tension feedback or winding diameter
- Web break protection in case of material breakage

Optidrive P2 Provides:

- PID Closed Loop Tension Control with feedback from a load cell or dancer arm
- Open Loop Vector control provides optimum control of the output torque level
- Encoder feedback option allows for a very wide speed range, even down to zero speed
- Safe Torque Off input immediately disables the drive in Emergency conditions


Options & Accessories

Installation options, plug-in modules and commissioning tools



Modbus RTU and CANopen on board as standard

For additional communication interfaces or functionality a range of plug-in modules is available:



Fieldbus Interfaces



Profibus DP
OPT-2-PROFB-IN



DeviceNet
OPT-2-DEVNT-IN



Ethernet IP
OPT-2-ETHNT-IN



Modbus TCP
OPT-2-MODIP-IN



Profinet
OPT-2-PFNET-IN



EtherCat
OPT-2-ETCAT-IN



Plug-in Options



Encoder Feedback

OPT-2-ENCOD-IN (5 Volt)
OPT-2-ENCHT-IN (15 – 30 Volt)

Closed loop encoder feedback, compatible with a wide range of incremental encoders

Extended I/O

OPT-2-EXTIO-IN

- Additional 3 Digital Inputs
- Additional Relay Output

Extended Relay

OPT-2-CASCD-IN

Additional 3 Relay Outputs:

Relay 3 – Drive Healthy Indication
Relay 4 – Drive Fault Indication
Relay 5 – Drive Running Indication

Functions are programmable / adjustable

Installation & Peripheral Options

A range of external EMC Filters, Brake Resistors, Input Chokes and Output Filters are available, to suit all installation requirements

Optistick Smart



NFC


Bluetooth®

Rapid Commissioning Tool

- Allows copying, backup and restore of drive parameters
- Provides Bluetooth interface to a PC running OptiTools Studio or the OptiTools Mobile app on a smartphone
- Onboard NFC (Near Field Communication) for rapid data transfer

OPT-3-STICK-IN

OptiTools Studio



Powerful PC Software

Drive commissioning and parameter backup

- Real-time parameter editing
- Drive network communication
- Parameter upload, download and storage
- Simple PLC function programming
- Real-time scope function and data logging
- Real-time data monitoring


Compatible with:

Windows Vista
Windows 7
Windows 8
Windows 8.1
Windows 10

Replace # in model code with
enclosure/display option

	kW	Amps	Frame Size	KW Model Code	Product Family	Generation	Frame Size	Voltage Code	Power Rating Code	Supply Phases	EMC Filter	Brake Transistor	IP20 Cabinet Mount	IP55 TFT Display	Indoor IP66 Non-Switched	Indoor IP66 Switched	Outdoor IP66 Non-Switched	Outdoor IP66 Switched
200-240V±10% 1 Phase Input	0.75	4.3	2	ODP - 2 - 2 2 075 - 1 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	1.5	7	2	ODP - 2 - 2 2 150 - 1 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	2.2	10.5	2	ODP - 2 - 2 2 220 - 1 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
200-240V±10% 3 Phase Input	0.75	4.3	2	ODP - 2 - 2 2 075 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	1.5	7	2	ODP - 2 - 2 2 150 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	2.2	10.5	2	ODP - 2 - 2 2 220 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	4	18	3	ODP - 2 - 3 2 040 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	5.5	24	3	ODP - 2 - 3 2 055 - 3 K F 4 #									2-MN			A-MN	B-MN	
	5.5	24	4	ODP - 2 - 4 2 055 - 3 K F 4 #									N-MN					
	7.5	30	4	ODP - 2 - 4 2 075 - 3 K F 4 #									2-MN	N-MN		A-MN	B-MN	
	11	46	4	ODP - 2 - 4 2 110 - 3 K F 4 #									2-MN	N-MN		A-MN	B-MN	
	15	60	5	ODP - 2 - 5 2 150 - 3 K F 4 #									2-MN	N-MN				
	18.5	72	5	ODP - 2 - 5 2 185 - 3 K F 4 #									2-MN	N-MN				
	22	90	6	ODP - 2 - 6 2 022 - 3 K F 4 #									N-MN					
	22	90	6A	ODP - 2 - 6 2 022 - 3 K F 4 #									2-MN					
	30	110	6	ODP - 2 - 6 2 030 - 3 K F 4 #									2-MN					
	30	110	6A	ODP - 2 - 6 2 030 - 3 K F 4 #									N-MN					
	37	150	6	ODP - 2 - 6 2 037 - 3 K F 4 #									2-MN					
	37	150	6B	ODP - 2 - 6 2 037 - 3 K F 4 #									N-MN					
	45	180	6	ODP - 2 - 6 2 045 - 3 K F 4 #									2-MN					
	45	180	6B	ODP - 2 - 6 2 045 - 3 K F 4 #									N-MN					
	55	202	7	ODP - 2 - 7 2 055 - 3 K F 4 #									N-MN					
	75	248	7	ODP - 2 - 7 2 075 - 3 K F 4 #									N-MN					
380-480V±10% 3 Phase Input	0.75	2.2	2	ODP - 2 - 2 4 075 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	1.5	4.1	2	ODP - 2 - 2 4 150 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	2.2	5.8	2	ODP - 2 - 2 4 220 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	4	9.5	2	ODP - 2 - 2 4 400 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	5.5	14	3	ODP - 2 - 3 4 055 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	7.5	18	3	ODP - 2 - 3 4 075 - 3 K F 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	11	24	3	ODP - 2 - 3 4 110 - 3 K F 4 #									2-MN			A-MN	B-MN	
	11	24	4	ODP - 2 - 4 4 110 - 3 K F 4 #									N-MN					
	15	30	4	ODP - 2 - 4 4 150 - 3 K F 4 #									2-MN	N-MN		A-MN	B-MN	
	18.5	39	4	ODP - 2 - 4 4 185 - 3 K F 4 #									2-MN	N-MN		A-MN	B-MN	
	22	46	4	ODP - 2 - 4 4 220 - 3 K F 4 #									2-MN	N-MN		A-MN	B-MN	
	30	61	5	ODP - 2 - 5 4 300 - 3 K F 4 #									2-MN	N-MN				
	37	72	5	ODP - 2 - 5 4 370 - 3 K F 4 #									2-MN	N-MN				
	45	90	6	ODP - 2 - 6 4 045 - 3 K F 4 #									N-MN					
	45	90	6A	ODP - 2 - 6 4 045 - 3 K F 4 #									2-MN					
	55	110	6	ODP - 2 - 6 4 055 - 3 K F 4 #									N-MN					
	55	110	6A	ODP - 2 - 6 4 055 - 3 K F 4 #									2-MN					
	75	150	6	ODP - 2 - 6 4 075 - 3 K F 4 #									N-MN					
	75	150	6B	ODP - 2 - 6 4 075 - 3 K F 4 #									2-MN					
	90	180	6	ODP - 2 - 6 4 090 - 3 K F 4 #									N-MN					
	90	180	6B	ODP - 2 - 6 4 090 - 3 K F 4 #									2-MN					
	110	202	6B	ODP - 2 - 6 4 110 - 3 K F 4 #									N-MN					
	110	202	7	ODP - 2 - 7 4 110 - 3 K F 4 #									2-MN					
	132	240	7	ODP - 2 - 7 4 132 - 3 K F 4 #									N-MN					
	160	302	7	ODP - 2 - 7 4 160 - 3 K F 4 #									N-MN					
	200	370	8	ODP - 2 - 8 4 200 - 3 K F 4 #									2-MN					
	250	450	8	ODP - 2 - 8 4 250 - 3 K F 4 #									N-MN					
480-525V±10% 3 Phase Input	132	185	7	ODP - 2 - 7 5 132 - 3 K 0 4 #									N-MN					
	150	205	7	ODP - 2 - 7 5 150 - 3 K 0 4 #									N-MN					
	185	255	7	ODP - 2 - 7 5 185 - 3 K 0 4 #									N-MN					
	200	275	7	ODP - 2 - 7 5 200 - 3 K 0 4 #									N-MN					
500-600V±10% 3 Phase Input	0.75	2.1	2	ODP - 2 - 2 6 075 - 3 K 0 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	1.5	3.1	2	ODP - 2 - 2 6 150 - 3 K 0 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	2.2	4.1	2	ODP - 2 - 2 6 220 - 3 K 0 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	4	6.5	2	ODP - 2 - 2 6 400 - 3 K 0 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	5.5	9	2	ODP - 2 - 2 6 550 - 3 K 0 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	7.5	12	3	ODP - 2 - 3 6 075 - 3 K 0 4 #									2-MN	X-TN	Y-TN	A-MN	B-MN	
	11	17	3	ODP - 2 - 3 6 110 - 3 K 0 4 #									2-MN			A-MN	B-MN	
	15	22	3	ODP - 2 - 3 6 150 - 3 K 0 4 #									2-MN			A-MN	B-MN	
	15	22	4	ODP - 2 - 4 6 150 - 3 K 0 4 #									N-MN					
	18.5	28	4	ODP - 2 - 4 6 185 - 3 K 0 4 #									2-MN	N-MN		A-MN	B-MN	
	22	34	4	ODP - 2 - 4 6 220 - 3 K 0 4 #									2-MN	N-MN		A-MN	B-MN	
	30	43	4	ODP - 2 - 4 6 300 - 3 K 0 4 #									2-MN	N-MN		A-MN	B-MN	
	37	54	5	ODP - 2 - 5 6 370 - 3 K 0 4 #									2-MN	N-MN				
	45	65	5	ODP - 2 - 5 6 450 - 3 K 0 4 #									2-MN	N-MN				
	55	78	6	ODP - 2 - 6 6 055 - 3 K 0 4 #									N-MN					
	75	105	6	ODP - 2 - 6 6 075 - 3 K 0 4 #									N-MN					
	90	130	6	ODP - 2 - 6 6 090 - 3 K 0 4 #									N-MN					
	110	150	6	ODP - 2 - 6 6 110 - 3 K 0 4 #									N-MN					


Model Code Guide



Drive Specification

Input Ratings		Supply Voltage 380 - 480V ± 10% 500 - 600V ± 10%	200 - 240V ± 10% 380 - 480V ± 10% 500 - 600V ± 10%
Supply Frequency		48 - 62Hz	
Displacement Power Factor		> 0.98	
Phase Imbalance		3% Maximum allowed	
Inrush Current		< rated current	
Power Cycles		120 per hour maximum, evenly spaced	
Output Ratings		230V 1Ph. Input: 0.75-2.2kW (1-3HP) 400V 3Ph. Input: 0.75-75kW (1-100HP) 460V 3Ph. Input: 1-350HP 575V 3Ph. Input: 0.75-110kW (1-150HP)	
Overload Capacity		150% for 60 seconds	
Output Frequency		0 - 500Hz, 0.1Hz resolution	
Acceleration Time		0.01 - 600 seconds	
Deceleration Time		0.01 - 600 seconds	
Typical Efficiency		> 98%	
Ambient Conditions		Temperature: -40 to 60°C Operating: -10 to 50°C	
Altitude		Up to 1000m ASL without derating Up to 2000m maximum UL Approved Up to 4000m maximum (non UL)	
Humidity		95% Max, non condensing	
Vibration		Conforms to IEC 60068-2-6 Sinusoidal Vibration 10 - 57Hz @ 0.075mm Pk 57 - 150Hz @ 1g Pk	
Enclosure	Ingress Protection	IP20, IP55, IP66	
Programming		Built-in keypad as standard Optional remote mountable keypad	
Display		Built-in multi language text display	
PC		OptiTools Studio	
Control Specification		V/F Voltage Vector Energy Optimised V/F 3GV Sensorless Vector Speed Control 3GV Sensorless Vector Torque Control Closed Loop (Encoder) Speed Control Closed Loop (Encoder) Torque Control PM Vector Control BLDC Control Synchronous Reluctance	
Control Method		4-32kHz Effective	
Stopping Mode		Ramp to Stop: User Adjustable 0.01 - 600 secs Coast to Stop	
Braking		Motor Flux Braking Built-in Braking Transistor	
Skip Frequency		Single point, user adjustable	
Setpoint Control		Analog Signal Digital	0 to 10 Volts 10 to 0 Volts -10 to +10 Volts 0 to 20mA 20 to 0mA 4 to 20mA 20 to 4mA PTC Motorised Potentiometer (Keypad & Terminal) Modbus RTU CANopen

Connection Diagram



Fieldbus Connectivity		Built-in	CANopen	125 - 1000kbps
Optional	Modbus RTU	9.6 - 115.2 kbps selectable 8N1, 8N2, 8E1, 8O1	PROFIBUS DP [DPV1] PROFINET IO DeviceNet EtherNet/IP EtherCAT Modbus TCP	
	Other			
I/O Specification	Power Supply	24 Volt DC, 100mA, Short Circuit Protected 10 Volt DC, 10mA for Potentiometer		
	Programmable Inputs	5 Total as standard (Optional additional 3) 3 Digital (Optional additional 3) 2 Analog / Digital Selectable 5 Digital With CAN IO Option		
	Digital Inputs	Opto - Isolated 8 - 30 Volt DC, internal or external supply Response time < 4ms		
	Analog Inputs	Resolution: 12 bits Response time: < 4ms Accuracy: < 1% full scale Parameter adjustable scaling and offset		
	PTC Input	Motor PTC / Thermistor Input Trip Level : 3kΩ		
	Programmable Outputs	7 Total (Optional additional 3) 2 Analog / Digital 2 Relays (Optional additional 3) 3 With CAN IO Option Module		
	Relay Outputs	Maximum Voltage: 250 VAC, 50 VDC Switching Current Capacity: 5A AC , 5A DC		
	Analog Outputs	0 to 10 Volt 0 to 20mA 4 to 20mA		
Application Features	PID Control	Internal PID Controller Multi Setpoint Select Standby / Sleep Mode Boost Function		
	Hoist Mode	Dedicated Hoist Mode Motor Holding Brake Pre-Torque & Control Over Limit Protection		
Maintenance & Diagnostics	Fault Memory	Last 4 Trips stored with time stamp Logging of data prior to trip for diagnostic purposes: Output Current Drive Temperature DC Bus Voltage Plus more in Optitools		
	Data Logging			
	Maintenance Indicator	Maintenance Indicator with user adjustable maintenance interval Onboard service life monitoring		
	Monitoring	Hours Run Meter Resettable & Non Resettable kWh meters Cooling Fan Run Time		
Standards Compliance	Low Voltage Directive	2014/35/EU		
	EMC Directive	2014/30/EU		
	Additional Conformance	UL, cUL, EAC, RCM		
	Marine Certification	DNV Type Approval		
	Environmental Conditions	Designed to meet IEC 60721-3-3, in operation: IP20 Drives: 3S2/3C2 IP55 & 66 Drives: 3S3/3C3		

NOT TO SCALE



Size	IP20							IP66							IP55								
mm Height	2	3	4	5	6A	6B	8	mm Width	2	3	4	4	5	6	7	mm Depth	257	310	360	450	540	865	1280
kg Weight	221	261	418	486	614	726	995	mm Height	110	131	172	233	286	330	480	mm Width	188	211	240	171	235	330	330
mm Depth	185	205	240	260	320	320	477	kg Weight	1.8	3.5	9.2	18.1	32	43	130	mm Height	182	235	271	252	270	332	358

Invertek Drives Ltd is dedicated to the design, manufacture and marketing of electronic variable speed drives. The state of the art UK headquarters houses specialist facilities for research & development, manufacturing and global marketing. The company pledges to implement and operate the ISO 14001 Environmental Management System to enhance environmental performance.

All company operations are accredited to the exacting customer focused ISO 9001:2008 quality standard. The company's products are sold globally in over 80 different countries. Invertek Drives' unique and innovative drives are designed for ease of use and meet with recognised international design standards.



Global Drive Solutions

Invertek Drives operate at the heart of automated systems around the world



Crane Control

Demanding application at South African mine



Machine Tool OEM

UK machine tool supplier specifies Optidrive



Film Manufacturing

Optimum tension control in Australia



Food Processing

Precision conveyor control in Spain



Amusement Parks

Reliable control of difficult loads in Spain



Optidrive P2 User Guide



Scan to download or visit the Invertek Drives website

www.invertekdrives.com/variable-frequency-drives/optidrive-p2

INVERTEK DRIVES LIMITED UK Headquarters

Offa's Dyke Business Park
Welshpool, Powys, UK
SY21 8JF

Tel: +44 (0)1938 556868
Fax: +44 (0)1938 556869
Email: sales@invertekdrives.com

